

Data Sheet

Strawhat LED

Hi-LED



Table of Contents

General Informations:	3
Electrical and Flux Characteristics	4
Color Wavelength Diagram:	6
Mechanical Dimensions:	7
Electrical Connection:.....	7
Optical Characteristics:.....	7
Packing:.....	8

General Informations:

Features:

- High intensity
- Reliable and rugged
- Low current requirement
- IC compatible

Application :

- Reading light
- Portable flashlight
- Up-lighters and Down-lighters
- LCD backlights
- General lighting
- Contour lights
- Ceiling lights
- Garden lighting
- Decoration lights
- Architectural lighting
- Beacon lights

Electrical and Flux Characteristics:

Table 1: Flux Characteristics

Code	Size(mm)	Case	Color	Wavelength	Angle
2718	4.8	Dip LED	Red	620-625 nm	120°
2780	4.8	Dip LED	Red	620-630 nm	120°
2725	4.8	Dip LED	Yellow	585-595 nm	120°
2707	4.8	Dip LED	Blue	464-473 nm	120°
2701	4.8	Dip LED	Green	515-521 nm	120°
2700	4.8	Dip LED	Warm White	3500 K	120°
2729	4.8	Dip LED	Cold White	7800 K	120°

Notes for Table 1:

1. Parts are tested in pulsed conditions, T_j = 25°C. Pulse width is 10 ms at rated test current.
2. İlker Elektronik maintains a ± 10% tolerance on flux measurements.
3. Typical R9 value for 80CRI can be change with 90CRI.
4. Center beam candle power is a calculated value based on Lambertian radiation pattern at nominal test current.

Table 2: Electrical Characteristics

Code	Color	Typical Forward Current (mA)	Min Input Voltage (CV)	Max Input Voltage (CV)	Typical Lm	Max Lm
2718	Red	20mA	1.8V	2V	350 mcd	500 mcd
2780	Red	20mA	1.9V	2.4V	800 mcd	1000 mcd
2725	Yellow	20mA	1.8V	3.4V	500 mcd	800 mcd
2707	Blue	20mA	3V	3.4V	500 mcd	800 mcd
2701	Green	20mA	3V	3.4V	200 mcd	5000 mcd
2700	Warm White	20mA	3V	3.4V	1500 mcd	2000 mcd
2729	Cold White	20mA	3V	3.4V	1500 mcd	2000 mcd

Notes for Table 2:

1. Parts are tested in pulsed conditions, T_j = 25°C. Pulse width is 10 ms at rated test current.
2. İlker Elektronik maintains a ± 10% tolerance on Current values.
3. Typical stabilized DC performance values are provided as reference only and are not a guarantee of performance.

Absolute Maximum Ratings ($T_A = 25^\circ \text{C}$ unless otherwise noted)

Table 3: Maximum Ratings

Parameter	Maximum Performance
Storage Temperature Range	-40 ~ +100° C
Operating Temperature Range	-25 ~ +85° C
Mounting Surface Temperature	60° C
LED Junction Temperature ¹	125° C
Electrostatic Discharge Classification (JEDEC-JESD22-A114F)	Class 1C
Reverse Voltage ^[2,3]	-5V
UL Recognition	UL recognized

Notes for Table 3:

1. Proper current de-rating must be observed to maintain junction temperature below the maximum.
2. Power LEDs are not designed to be driven in reverse bias.
3. At maximum reverse current of 10 μ A/LED.

Application Notes:


- The Anode side of the device is denoted by a hole in the lead frame.
- Electrical insulation between the case and the board is required. Do not electrically connect either the anode or cathode to the slug.
- Drawing not to scale.
- All dimensions are in millimeters.
- Unless otherwise indicated, tolerances are $\pm 0.20\text{mm}$.
- Please do not bend the leads of the LED, otherwise it will damage the LED.

Precautions:


- Current should be derated in order to keep junction temperature below maximum by reducing power dissipation.
- Current spikes should be avoided especially during power up. It is good practice to initially connect PCB to unactivated supply, then gradually ramp up voltage to desired value.
- Proper management of the thermal path should be observed. Adequate heatsinking of strip should be provided in order to maintain junction temperature below maximum. Proper thermal conduction layers should be introduced at all interfaces to prevent insulating air gaps in the thermal path.
- As with all semiconductor devices, it is good practice to avoid electrostatic discharge (ESD).

Color Wavelength Diagram:

LED Color Spectrum for Red, Green, Blue, Yellow:



LED Color Spectrum for White (80 CRI) :




DO NOT LOOK DIRECTLY AT LED WITH UNSHIELDED EYES OR DAMAGE TO RETINA MAY OCCUR.

Mechanical Dimensions:


Technical Drawing:

2700




Electrical Connection:

Circuit Diagram:



Optical Characteristics:





Packing:



- Items per Carton: 80 Bags / Carton
- Package Measurements: 44X40X28 CM
- Gross Weight: 18.00 KG
- Package Type: Antistatic bag, carton box; usually 1000pcs per bag