
## 2835-B312 Module LEDs



	DC12V III Ip67
PRODUCT FEATURE	S:
Material and technology	: Using ultra bright 2835 bulb quality, Using Aluminum sheet, The
plastic injection	n process, beautiful appearance, unique, good heat dissipation effect
Lighting character :	View angle, color uniform, Light emitting angle up to 150
Lumen depreciation :	Good dissipation, no more than 5% after 50000h
Electrical safety :	Use 12v power supply, safety and reliable
Installation :	3M tape back of strip,ultrathin design
Use :	Advertising signs, outer glow word, building outline
	lighting, interior decoration etc



dimension diagram (unit:mm)

4


(<u>;</u>Ö;

ø

160\*

PRODUCT PARAMETER:		dimension diagram (unit:mm)
Power:	1.4 W/pcs	
Input voltage :	DC12V	
Waterproof rate :	I P 67	
Size :	82*18*7mm	
LM:	125-135 lm/pcs	
Led quantity/pcs :	3 led	
Module quantity/String :	20 pcs/String	
Color for choice :	W	
View angle: :	160°	
Weight:	1.5KG/100PCS	

## POWER SUPPLY INSTALLATION INSTRUCTION:



Power supply:	12v constant voltage
Power supply match:	suggest connect 1 power supply to each chain(20pcs module)
power supply connection :	attention the positive and negtive ,don't polarity reversed
Strip cutting:	3 led/pcs ,any length cutting for the pcs

## PRODUCT MODEL:

Model	color	working voltage	working current	power	view angle	led quantity/String	size(mm)	package	waterproof for choice
			0.11 0/200	1 414//200	160°		00*10*7	2000000/0000	I P 67
		DC 12V	0.11 A/pcs	1.4W/pcs	160°	60 LED	82*18*7	200pcs/pack	1 P 07



cw	15000K 125LM
ww	2800-3200K 129LM
R	620nm-35 im
G	527nm-90 lm
в	470nm-20 lm
Y	590nm-30 lm